

38-40 SERIES MEDIUM DUTY CASTERS



FEATURES:

- Finish – Bright Zinc plating
- Swivel – Double ball bearing with hardened raceways for extra strength
- Dust Cover – Helps protect swivel bearings
- Construction – Heavy gauge cold rolled steel, formed for strength
- Axle – 3/8" diameter bolt with lock nut
- King Pin – 1/2" steel rivet, hydraulically upset
- Optional Accessories

SERIES 38
STANDARD SIZE PIPE PLUGS
AVAILABLE:
 3/4" - 1" - 1 1/4"
 Please specify size desired.

SERIES 40
RUBBER APPLICATOR SERIES
 Available to fit 7/8" to 17/8" I.D. tubing.
 Please specify exact tubing I.D. or O.D.
 and gauge.

| WHEEL | | | | CAPACITY | LOAD HEIGHT | SWIVEL RADIUS | CASTER ORDERING NUMBER | | APP. WEIGHT |
|----------|-------------|----------------------|---------|----------|-------------|---------------|------------------------|----------------------|-------------|
| DIAMETER | TREAD WIDTH | TYPE | BEARING | POUNDS | INCHES | INCHES | SERIES 38 PIPE PLUG | SERIES 40 APPLICATOR | POUNDS |
| 2 1/2 | 1 1/4 | Cushion Tread Rubber | Delrin | 140 | 3 7/16 | 2 3/4 | 21/2-38-105 | 21/2-40-105 | 1 11/16 |
| | | Hard Tread Rubber | Delrin | 210 | | | 21/2-38-106 | 21/2-40-106 | |
| | | Polyolefin | Plain | 210 | | | 21/2-38-513 | 21/2-40-513 | |
| 3 | 1 1/4 | Cushion Tread Rubber | Delrin | 150 | 4 5/16 | 3 | 3-38-105 | 3-40-105 | 13/4 |
| | | Hard Tread Rubber | Delrin | 220 | | | 3-38-106 | 3-40-106 | |
| | | Cushion Tread Rubber | Ball | 150 | | | 3-38-152 | 3-40-152 | |
| | | Hard Tread Rubber | Ball | 220 | | | 3-38-162 | 3-40-162 | |
| | | Semi-Steel | Plain | 300 | | | 3-38-120 | 3-40-120 | |
| | 1 1/2 | Polyolefin | Plain | 250 | | | 3-38-521 | 3-40-521 | |
| | | Phenolic | Plain | 300 | | | 3-38-121 | 3-40-121 | |
| | | Phenolic | Roller | 300 | | | 3-38-221 | 3-40-221 | |
| | | | | | | | | | |
| 3 1/2 | 1 1/4 | Cushion Tread Rubber | Delrin | 160 | 4 7/16 | 3 1/4 | 31/2-38-105 | 31/2-40-105 | 2 |
| | | Hard Tread Rubber | Delrin | 230 | | | 31/2-38-106 | 31/2-40-106 | |
| | | Cushion Tread Rubber | Ball | 160 | | | 31/2-38-452 | 31/2-40-452 | |
| | | Hard Tread Rubber | Ball | 230 | | | 31/2-38-462 | 31/2-40-462 | 2 3/16 |
| | | Polyolefin | Plain | 250 | | | 31/2-38-513 | 31/2-40-513 | |
| | | Rubber Tire | Ball | 200 | | | 31/2-38-113 | 31/2-40-113 | |
| | | Gray Rubber Tire | Ball | 225 | | | 31/2-38-113G | 31/2-40-113G | |
| | | Polyurethane Tire | Ball | 250 | | | 31/2-38-113P | 31/2-40-113P | |
| | | Advantage Donut | Delrin | 225 | | | 31/2-38-314GD | 31/2-40-314GD | |
| | | Advantage Flat | Delrin | 250 | | | 31/2-38-314GF | 31/2-40-314GF | |
| | | Advantage Donut | Ball | 225 | | | 31/2-38-213GD | 31/2-40-213GD | |
| | | Advantage Flat | Ball | 250 | | | 31/2-38-213GF | 31/2-40-213GF | |
| | | Poly Loc Grey | Ball | 250 | | | 31/2-38-213G | 31/2-40-213G | |
| | | Poly Loc Grey | Delrin | 250 | | | 31/2-38-314G | 31/2-40-314G | |
| | | Poly Loc Poly | Ball | 250 | | | 31/2-38-213P | 31/2-40-213P | |
| | | Semi-Steel | Plain | 300 | | | 31/2-38-120 | 31/2-40-120 | |

38-40 SERIES MEDIUM DUTY CASTERS

| WHEEL | | | | CAPACITY | LOAD HEIGHT | SWIVEL RADIUS | CASTER ORDERING NUMBER | | APP. WEIGHT | | | | | |
|----------------------|-------------|----------------------|----------|----------------------|-------------|---------------|------------------------|----------------------|-------------|--------|---|----------|----------|-------|
| DIAMETER | TREAD WIDTH | TYPE | BEARING | POUNDS | INCHES | INCHES | SERIES 38 PIPE PLUG | SERIES 40 APPLICATOR | POUNDS | | | | | |
| 4 | 1 1/4 | Cushion Tread Rubber | Delrin | 170 | 4 15/16 | 3 1/2 | 4-38-105 | 4-40-105 | 2 3/8 | | | | | |
| | | Hard Tread Rubber | Delrin | 250 | | | 4-38-106 | 4-40-106 | | | | | | |
| | | Cushion Tread Rubber | Ball | 170 | | | 4-38-452 | 4-40-452 | | | | | | |
| | | Hard Tread Rubber | Ball | 250 | | | 4-38-462 | 4-40-462 | | | | | | |
| | | Rubber Tire | Ball | 200 | | | 4-38-113 | 4-40-113 | 2 1/2 | | | | | |
| | | Grey Rubber Tire | Ball | 200 | | | 4-38-113G | 4-40-113G | | | | | | |
| | | Polyurethane Tire | Ball | 275 | | | 4-38-113P | 4-40-113P | | | | | | |
| | | Advantage Donut | Delrin | 250 | | | 4-38-314GD | 4-40-314GD | | | | | | |
| | | Advantage Flat | Delrin | 300 | | | 4-38-314GF | 4-40-314GF | | | | | | |
| | | Advantage Donut | Ball | 250 | | | 4-38-213GD | 4-40-213GD | | | | | | |
| | | Advantage Flat | Ball | 300 | | | 4-38-213GF | 4-40-213GF | | | | | | |
| | | Poly Loc Grey | Ball | 275 | | | 4-38-213G | 4-40-213G | | | | | | |
| | | Poly Loc Grey | Delrin | 275 | | | 4-38-314G | 4-40-314G | | | | | | |
| | | Poly Loc Poly | Ball | 275 | | | 4-38-213P | 4-40-213P | | | | | | |
| | Polyolefin | Plain | 275 | 4-38-513 | | | 4-40-513 | | | | | | | |
| | Semi-Steel | Plain | 300 | 4-38-120 | | | 4-40-120 | | | | | | | |
| | 1 1/2 | Phenolic | Plain | 300 | | | 4-38-121 | 4-40-121 | | | | | | |
| | | Phenolic | Roller | 300 | | | 4-38-221 | 4-40-221 | | | | | | |
| | | 5 | 1 1/4 | Cushion Tread Rubber | | | Delrin | 200 | | 6 1/16 | 4 | 5-38-105 | 5-40-105 | 2 3/4 |
| | | | | Hard Tread Rubber | | | Delrin | 280 | | | | 5-38-106 | 5-40-106 | |
| Conductive Rubber | | | | Self-lube | 200 | 5-38-105C | 5-40-105C | | | | | | | |
| Neoprene | | | | Delrin | 200 | 5-38-105N | 5-40-105N | | | | | | | |
| Grey Rubber | Delrin | | | 200 | 5-38-105G | 5-40-105G | | | | | | | | |
| Cushion Tread Rubber | Ball | | | 200 | 5-38-152 | 5-40-152 | | | | | | | | |
| Hard Tread Rubber | Ball | | | 280 | 5-38-162 | 5-40-162 | | | | | | | | |
| Cushion Tread Rubber | Ball | | | 200 | 5-38-452 | 5-40-452 | | | | | | | | |
| Hard Tread Rubber | Ball | | | 280 | 5-38-462 | 5-40-462 | | | | | | | | |
| Rubber Tire | Ball | | | 200 | 5-38-113 | 5-40-113 | 3 | | | | | | | |
| Grey Rubber Tire | Ball | | | 200 | 5-38-113G | 5-40-113G | | | | | | | | |
| Polyurethane Tire | Ball | | | 300 | 5-38-113P | 5-40-113P | | | | | | | | |
| Advantage Donut | Delrin | | | 250 | 5-38-314GD | 5-40-314GD | | | | | | | | |
| Advantage Flat | Delrin | | | 325 | 5-38-314GF | 5-40-314GF | | | | | | | | |
| Advantage Donut | Ball | | 250 | 5-38-213GD | 5-40-213GD | | | | | | | | | |
| Advantage Flat | Ball | | 325 | 5-38-213GF | 5-40-213GF | | | | | | | | | |
| Poly Loc Grey | Ball | | 300 | 5-38-213G | 5-40-213G | | | | | | | | | |
| Poly Loc Grey | Delrin | | 300 | 5-38-314G | 5-40-314G | | | | | | | | | |
| Poly Loc Poly | Ball | | 300 | 5-38-213P | 5-40-213P | | | | | | | | | |
| Polyolefin | Plain | | 300 | 5-38-513 | 5-40-513 | | | | | | | | | |
| Polyolefin | Ball | 300 | 5-38-514 | 5-40-514 | | | | | | | | | | |
| Semi-Steel | Plain | 300 | 5-38-120 | 5-40-120 | | | | | | | | | | |
| 1 1/2 | Phenolic | Plain | 300 | 5-38-121 | 5-40-121 | | | | | | | | | |
| | Phenolic | Roller | 300 | 5-38-221 | 5-40-221 | | | | | | | | | |

38-40 SERIES MEDIUM DUTY CASTERS

| WHEEL | | | | CAPACITY | LOAD HEIGHT | SWIVEL RADIUS | CASTER ORDERING NUMBER | | APP. WEIGHT |
|----------|-------------|----------------------|-----------|----------|-------------|---------------|------------------------|----------------------|-------------|
| DIAMETER | TREAD WIDTH | TYPE | BEARING | POUNDS | INCHES | INCHES | SERIES 38 PIPE PLUG | SERIES 40 APPLICATOR | POUNDS |
| 6 | 1 1/4 | Cushion Tread Rubber | Delrin | 220 | 7 1/16 | 4 1/2 | 6-38-105 | 6-40-105 | 3 1/8 |
| | | Hard Tread Rubber | Delrin | 300 | | | 6-38-106 | 6-40-106 | |
| | | Conductive Rubber | Self-lube | 220 | | | 6-38-105C | 6-40-105C | |
| | | Neoprene | Delrin | 220 | | | 6-38-105N | 6-40-105N | |
| | | Cushion Tread Rubber | Ball | 220 | | | 6-38-152 | 6-40-152 | |
| | | Hard Tread Rubber | Ball | 300 | | | 6-38-162 | 6-40-162 | |
| | | Rubber Tire | Ball | 250 | | | 6-38-113 | 6-40-113 | 3 3/4 |
| | | Grey Rubber Tire | Ball | 250 | | | 6-38-113G | 6-40-113G | |
| | | Polyurethane Tire | Ball | 300 | | | 6-38-113P | 6-40-113P | |
| | | Advantage Donut | Delrin | 300 | | | 6-38-314GD | 6-40-314GD | |
| | | Advantage Donut | Ball | 300 | | | 6-38-213GD | 6-40-213GD | |
| | | Poly Loc Grey | Ball | 300 | | | 6-38-213G | 6-40-213G | |
| | | Poly Loc Grey | Delrin | 300 | | | 6-38-314G | 6-40-314G | |
| | | Poly Loc Poly | Ball | 300 | | | 6-38-213P | 6-40-213P | |
| | 1 1/2 | Phenolic | Plain | 300 | | | 6-38-121 | 6-40-121 | |
| | | Phenolic | Roller | 300 | | | 6-38-221 | 6-40-221 | |
| | | Polyolefin | Plain | 300 | | | 6-38-521 | 6-40-521 | |

NOTE: Add 3/8" to load height for 38 Series casters.