

45-46 SERIES MEDIUM DUTY CASTERS



- Hardened raceway for strenght
- Corrosion-resistant zinc plate finish
- Nut and bolt king pin
- Zerk fittings in wheel and swivel bearings
- Legs welded by machine for uniform consistency and strenght
- Wide selection of wheels for a wide selection of applications
- Swivel radius is set for maximum maneuverability under a full load
- 2" fork spacing
- Ideal for: Stock Carts, Platform Trucks, Wire Shelving Units, Warehouses, Factories, Heavy Appliances (ovens, freezer, etc.)
- Heavy foodservice equipment

40 SERIES SPECIFICATIONS

WHEEL DIAMETER	WHEEL WIDTH	WHEEL COMPOSTITON	BEARING TYPE	LOAD CAPACITY	LOAD HEIGHT	SWIVEL RADIUS	PART NUMBER	
							SWIVEL	RIGID
4 (101.6)	1 1/2	Rubber / Cast Iron	Roller	300	5-5/8	3-19/16	445-08R	446-08R
		Polyurethane	Roller	600			445-10R	446-10R
		Heavy Duty Plastic	Ball	450			445-07R	446-07R
		Phenolic	Roller	600			445-05R	446-05R
		V-Grrove Steel	Roller	600			445-13R	446-13R
5 (127)	1 1/2	Rubber / Cast Iron	Roller	345	6-1/2	4 1/4	545-08R	546-08R
		Polyurethane	Roller	750			545-10R	546-10R
		Heavy Duty Plastic	Ball	550			545-07R	546-07R
		Phenolic	Roller	750			545-05R	546-05R
6 (152)	1 1/2	Rubber / Cast Iron	Roller	370	7-1/2	5	645-08R	646-08R
		Polyurethane	Roller	750			645-10R	646-10R
		Heavy Duty Plastic	Ball	600			645-07R	646-07R
		Phenolic	Roller	750			645-05R	646-05R

FASTENING SPECIFICATIONS

FASTENING TYPE	SPECIFICATION		
	OVERALL	HOLE SPACING SLOTTED	ATTACHING BOLT SIZE
Top Plate	4 x 4-1/2	2-5/8 x 3-5/8 To 3 x 3	3/8