

55-56 SERIES MEDIUM / HEAVY DUTY CASTERS



- Large top plate and raceways combine ease of swiveling and strength
- Corrosion-resistant zinc plated finish
- Nut and bolt king pin
- Zerk fittings in wheel and swivel bearings
- Legs welded by machine for uniform consistency and strength
- 2 1/2 fork spacing
- Applications include: Large platform trucks, Freight terminal trucks, Cargo containers, Drying racks

55-56 SERIES SPECIFICATIONS

WHEEL DIAMETER	WHEEL WIDTH	WHEEL COMPOSTITON	BEARING TYPE	LOAD CAPACITY	LOAD HEIGHT	SWIVEL RADIUS	PART NUMBER	
							SWIVEL	RIGID
4	2	Rubber / Cast Iron	Roller	350	5-5/8	3-13/16	455-08R	456-08R
		Polyurethane	Roller	700			455-10R	456-10R
		Heavy Duty Plastic	Roller	500			455-07R	456-07R
		Phenolic	Roller	700			455-05R	456-05R
		Steel	Roller	700			455-03R	456-03R
		V-Groove Steel	Roller	700			455-13R	456-13R
		Gray Rubber / Plastic	Roller	300			455-25R	456-25R
5	2	Rubber / Cast Iron	Roller	375	6-1/2	4	555-08R	556-08R
		Polyurethane	Roller	1000			555-10R	556-10R
		Polyurethane on Plastic	Roller	500			555-12R	556-12R
		Heavy Duty Plastic	Roller	600			555-07R	556-07R
		Phenolic	Roller	1000			555-05R	556-05R
		Steel	Roller	1000			555-03R	556-03R
		V-Groove Steel	Roller	1000			555-13R	556-13R
		Gray Rubber / Plastic	Roller	350			555-25R	556-25R
6	2	Rubber / Cast Iron	Roller	440	7-1/2	4-3/4	655-08R	656-08R
		Rubber / Aluminum	Roller	440			655-09R	656-09R
		Polyurethane	Roller	1200			655-10R	656-10R
		Polyurethane on Plastic	Roller	650			655-12R	656-12R
		Heavy Duty Plastic	Roller	700			655-07R	656-07R
		Phenolic	Roller	1200			655-05R	656-05R
		Steel	Roller	1200			655-03R	656-03R
		V-Groove Steel	Roller	1200			655-13R	656-13R
		Gray Rubber / Plastic	Roller	410			655-25R	656-25R
8	2	Rubber / Cast Iron	Roller	500	9-1/8	6-1/4	855-08R	856-08R
		Rubber / Aluminum	Roller	500			855-09R	856-09R
		Polyurethane	Roller	1400			855-10R	856-10R
		Polyurethane on Plastic	Roller	750			855-12R	856-12R
		Phenolic	Roller	1400			855-05R	856-05R
		Steel	Roller	1400			855-03R	856-03R
		Gray Rubber / Plastic	Roller	500			855-25R	856-25R

FASTENING SPECIFICATIONS

FASTENING TYPE	FASTENING SPECIFICATION		
	OVERALL SIZE	HOLE SPACING SLOTTED	ATTACHING BOLT SIZE
Top Plate	4-1/2 x 6-1/4	2-7/16 x 4-15/16 to 3-3/8 x 5-1/4	3/8

OPTIONS FOR 55 AND 56 SERIES

ACCESSORIES CODE	DESCRIPTION
DW	Double Welded Forks.
VLB	Verti-Lock Brake
<i>Add selected code or codes to the end of part number.</i>	