

70-71 SERIES HEAVY DUTY CASTERS



- Large top plate and raceways combine ease of swiveling and strength.
- Corrosion-resistant zinc plated finish.
- 3/4" nut and bolt king pin.
- Zerk fittings in wheel and swivel bearings.
- Legs welded by machine for uniform consistency and strength.
- 3" fork spacing (Leg thickness: 23/64").
- 3/4" diameter axle and lock nut.
- Applications include:
 - Large platform trucks.
 - Freight terminal trucks.
 - Cargo containers.
 - Drying racks.

70-71 SERIES SPECIFICATIONS

WHEEL DIAMETER	WHEEL WIDTH	WHEEL COMPOSITION	BEARING TYPE	LOAD CAPACITY	LOAD HEIGHT	SWIVEL RADIUS	PART NUMBER	
							SWIVEL	RIGID
6	2-1/2	Rubber / Cast Iron	Roller	600	7-1/2	4-3/4	670-08R	671-08R
		Polyurethane	Roller	1600			670-10R	671-10R
		Phenolic	Roller	1600			670-05R	671-05R
		Steel	Roller	1600			670-03R	671-03R
8	2-1/2	Rubber / Cast Iron	Roller	600	9-3/4	6 1/2	870-08R	871-08R
		Polyurethane	Roller	1600			870-10R	871-10R
		Phenolic	Roller	1600			870-05R	871-05R
		Steel	Roller	1600			870-03R	871-03R

FASTENING SPECIFICATIONS

FASTENING TYPE	FASTENING SHAPE	FASTENING CODE NO	FASTENING SPECIFICATION		
			OVERALL SIZE	HOLE SPACING SLOTTED	ATTACHING BOLT SIZE
Top Plate			4-1/2 x 6-1/4	2-7/16 x 4-15/16 To 3-3/8 x 5-1/4	3/8

OPTIONS FOR 70 AND 71 SERIES

ACCESSORIES CODE	DESCRIPTION
DW	Double Welded Forks

Add selected code or codes to the end of part number.