

# RA - RUBBER MOLD-ON ALUMINUM WHEELS



## CAPACITY TO 500 LBS.

- Soft rubber cushion tread
- Aluminum center
- Light in weight, yet strong
- Full floor protection
- High shock loads
- Minimum draw bar pull to start and sustain motion
- Durometer 70-80 (Shore A)

### 3 1/2 - 4 -5 in:

- Gray rubber tread is non-marking
- Attractive polished aluminum center
- Annular ball bearings are easy rolling

### 6 and 8 in:

- Low profile rubber tread
- Aluminum die cast center
- Roller bearing for smooth rolling and higher capacities
- For industrial and institutional applications

## SPECIFICATIONS

WHEEL DIAMETER	WHEEL WIDTH	WHEEL COMPOSITION	BEARING TYPE	LOAD CAPACITY	BEARING BORE	HUB LENGTH	PART NUMBER
3 1/2	1 1/4	Gr. Rubber	Annular	225	3/8	1 1/2	RAB-3514
4	1 1/4	Gr. Rubber	Annular	250	3/8	1 1/2	RAB-414
5	1 1/4	Gr. Rubber	Annular	250	3/8	1 1/2	RAB-514
6	2	Rubber	Roller	410	3/4	2 3/16	RAR-620
8	2	Rubber	Roller	500	3/4	2 3/16	RAR-820

*Delrin Bearings: Available on 6 and 8 in. wheels*