

# RC - RUBBER MOLD-ON CAST IRON WHEELS



## CAPACITY TO 700 LBS.

- Cushion rubber tread.
- Strong cast iron center.
- Full floor protection.
- High shock loads.
- Minimum draw bar pull to start and sustain motion.
- Zerk fittings in hub for lubrication.
- Rollere bearings for ease of maneuverability.
- Durometer 70-80 (SHORE A)

## SPECIFICATIONS

WHEEL DIAMETER	WHEEL WIDTH	WHEEL COMPOSITION	BEARING TYPE	LOAD CAPACITY	BEARING BORE	HUB LENGTH	PART NUMBER
4	1 1/2	Rubber/Cast Iron	Roller	250	3/4	1 5/8	RCR-415
	2		Roller	350	3/4	2 3/16	RCR-420
5	1 1/2	Rubber/Cast Iron	Roller	300	3/4	1 5/8	RCR-515
	2		Roller	375	3/4	2 3/16	RCR-520
6	1 1/2	Rubber/Cast Iron	Roller	300	3/4	1 5/8	RCR-615
	2		Roller	410	3/4	2 3/16	RCR-620
	2 1/2		Roller	550	1	2 3/4	RCR-625
	3		Roller	700	1	3/4	RCR-630
8	2	Rubber/Cast Iron	Roller	500	3/4	2 3/16	RCR-820
	2 1/2		Roller	700	1	2 3/4	RCR-825
	3		Roller	800	1	3	RCR-830
10	2 1/2	Rubber/Cast Iron	Roller	800	1	2 3/4	RCR-1025
	3		Roller	1000	1	3 1/4	RCR-1030
10	2 1/2	Rubber/Cast Iron	Roller	900	1	2 3/4	RCR-1225
	3		Roller	1140	1	3 1/4	RCR-1230
10	3	Rubber/Cast Iron	Roller	1450	1	3 1/4	RCR-1603