

SR - SOFT RUBBER WHEELS



CAPACITY TO 200 LBS.

- Soft rubber tread molded to a hard rubber core
- Cushion, quiet ride
- Protects floors
- Shock absorbent
- Tread durometer is 75 +/- 5 (shore A)

SPECIFICATIONS

WHEEL DIAMETER	WHEEL WIDTH	WHEEL COMPOSITION	BEARING TYPE	LOAD CAPACITY	BEARING BORE	HUB LENGTH	PART NUMBER
2	13/16	Soft Rubber	Nylon	65	1/4	7/8	SR-222
	1		Nylon	90	1/4	1 1/16	SR-212
2 1/2	13/16	Soft Rubber	Nylon	75	15/64	7/8	SR-2510
	1 1/8		Nylon	100	5/16	1 3/8	SR-252P
3	15/16	Soft Rubber	Nylon	100	1/4	1	SR-312
	13/16		Nylon	100	1/4	7/8	SR-310
	1		Nylon	100	5/16	1 5/32	SR-314
	1 1/4		Nylon	125	5/16	1 7/16	SR-331
	1 1/4		Nylon	125	3/8	1 7/16	SR-330
	1 1/4		Nylon	125	3/8	1 9/16	SR-325
	1 1/4		Ball	125	5 1/6	1 5/8	SR-331
	1 1/4		Ball	125	3/8	1 5/8	SR-330
3 1/2	1 1/4	Soft Rubber	Nylon	140	5/16	1 7/16	SR-3531
			Nylon	140	3/8	1 7/16	SR-3530
4	1	Soft Rubber	Nylon	125	5/16	1 5/32	SR-412
	1		Ball	125	5/16	1 5/32	SRB-412
	1 1/4		Nylon	165	5/16	1 7/16	SR-431
	1 1/4		Nylon	165	3/8	1 7/16	SR-430
	1 1/4		Nylon	165	3/8	1 9/16	SR-425
	1 1/4		Ball	165	5/16	1 5/8	SRB-431
	1 1/4		Ball	165	3/8	1 5/8	SRB-430
	1 1/4		Nylon	165	1/2	1 9/16	SR-432
	1 1/4		Nylon	165	7/16	1 15/16	SR-420
4	1	Soft Rubber	Nylon	125	5/16	1 5/32	SR-512
	1		Ball	125	5/16	1 5/32	SRB-512
	1 1/4		Nylon	175	5/16	1 7/16	SR-531
	1 1/4		Nylon	175	3/8	1 7/16	SR-530
	1 1/4		Nylon	175	3/8	1 9/16	SR-525
	1 1/4		Ball	175	5/16	1 5/8	SRB-531
	1 1/4		Ball	175	3/8	1 5/8	SRB-530